

IPOL LCM GREASE No. 2

Description:

A premium quality high temperature, long life, extreme pressure grease fortified with solid lubricants to impart added lubrication properties. This is a superior grade compared to clay based greases with solid lubricants.

Salient Features:

- Extreme pressure
- Longer life

Application:

- It is recommended for general ball, roller, needle & spherical bearings, spindles, operating at high speed, solid lubricants present in the grease provides enhanced lubrication, even when base grease dries up.

Benefits:

- These greases are suitable for high temperature applications upto 120°C for prolonged durations.
- Can be conveniently used in centralized lubrication systems.

Product Data

Typical Results: IPOL LCM GREASE No. 2

Characteristics	Test Methods	Results
Colour	Visual	BLACK
Texture	Visual	Smooth buttery
Base	-	Lithium Complex
Drop Point °C	ASTM D 5116	250 Min.
Worked Penetration 60 double stroke @25°C.	ASTM D 217	265 - 295
Water Washout Loss %.	ASTM D 1264	< 5
Four Ball Weld Load Test Kgs./min.	ASTM D 2596	300

The above data is typical & does not constitute a specification. The information provided is not to be taken as a warranty or representation for which we assume no legal responsibility, nor as permission or recommendation to practice any attended location or otherwise. It is solely offered for your consideration, investigation and verification.