

IPOL MGB HD OILS

Description:

IPOL MGB HD oils are manufactured using high Viscosity Index base oils fortified with Ashless Dispersant, Metallo-organic Detergents, Oxidation and Wear Inhibitors. **IPOL MGB HD** are multigrade oils available in viscosity classification SAE 10W-30, SAE 20W-40 and SAE 20W-50 grades.

Application:

IPOL MGB HD oils recommended for Diesel Engines designed for Truck, Bus and Marine usage and also recommended for use in vehicles operating in stop and go service such as Taxies, City Delivery Vehicles and Public Utility Fleets, Tractors, besides stationery Diesel and Petrol Engines.

Performance Levels:

- API CC/SC
- MIL-L-2104B (OBS)
- IS 13656-2002 type E-DL1/E-PL1

Benefits to Customer:

1. All round the year oil
2. Keeps engine clean.
3. Protects against wear and corrosion.
4. Easy Start up.

Product Data

TYPICAL RESULTS: IPOL MGB HD OILS

Sr. No.	TEST	Test Method	Results		
			SAE 10W30	SAE 20W40	SAE 20W50
1	Appearance	Visual	Clear & Bright		
2	Kinematic Viscosity @100°C	P: 25	10.0 - 12.0	13.5 - 15.0	17.0 - 18.5
3	Viscosity Index, min.	P: 56	130	110	115
4	Flash Point (COC), °C min.	P: 69	190	200	200
5	Pour Point, °C max.	P: 10	(-) 27	(-) 21	(-) 21
6	TBN, mg KOH/gm	P: 86	4.5	4.5	4.5
8	Sulphated Ash % mass	P: 4	0.65 max	0.65 max	0.65 max

The above data is typical & does not constitute a specification. The information provided is not to be taken as a warranty or representation for which we assume no legal responsibility, nor as permission or recommendation to practice any attended location or otherwise. It is solely offered for your consideration, investigation and verification.