

IPOL MCG DIESEL PREMIUM 15W-40**Description:**

IPOL MCG DIESEL PREMIUM 15W-40 is a high performance, multi grade diesel engine oil manufactured from imported/indigenous high quality base stocks. It is fortified with shear stable viscosity index improver and proven high performance engine oil additives.

Application:

IPOL MCG DIESEL PREMIUM 15W-40 is recommended for automotive diesel engines meeting Bharat Stage II/ Euro II emission norms operating on low sulphur fuels. It is designed for new generation on-road and off-road heavy duty vehicles, both naturally aspirated and/or turbo charged engines.

Performance Claims:

- *IPOL MCG DIESEL PREMIUM 15W-40* is manufactured to meet :
- API CG-4/SJ
- MB 228.3
- MAN 271
- MACK EO-L
- VOLVO VDS 2
- ACEA E3/B3/A3-96
- VW 501/505

• **Performance Benefits:**

Product Data

IPOL MCG DIESEL PREMIUM 15W-40 offers the following benefits :

1. Increases Engine Re-build life
2. Reduces Engine component and valve train wear.
3. Minimizes piston deposits.
4. Extended drain capability
5. Higher Thermal and Oxidation stability
6. Longer oil filter and Seal life

• **TYPICAL RESULTS: IPOL MCG DIESEL PREMIUM 15W-40 :-**

Characteristics	Test Method IS 1448	Result
Appearance	Visual	Clear & Bright
Kinematic Viscosity cSt at 100°C	P: 25	13.5 - 15.5
Viscosity Index, min.	P: 56	130
Flash Point (COC), °C min.	P: 69	220
Pour Point, °C max.	P: 10	(-) 24
TBN, Mg/KOH/gm, Min.	P: 86	10
Sulphated Ash % mass	P: 4	1.6 max.
Evaporative Loss, % Max.	P: 136	15
Foaming Tendency / stability Seq. II	P : 67	50/Nil

The above data is typical & does not constitute a specification. The information provided is not to be taken as a warranty or representation for which we assume no legal responsibility, nor as permission or recommendation to practice any attended location or otherwise. It is solely offered for your consideration, investigation and verification