

IPOL MTC DIESEL SUPER OILS

Description:

IPOL MTC DIESEL SUPER oils are Heavy Duty, mono grade oils namely SAE 10W, SAE 20, SAE 30, SAE 40 and SAE 50 diesel engine oils manufactured using high quality, solvent extracted paraffinic base oils fortified with performance proven engine oil additives.

Application:

IPOL MTC DIESEL SUPER oils are recommended for use in all turbo- charged/ super-charged / Naturally aspirated diesel engines used in Trucks and Buses of Tata Motors, Ashok Leyland, M&M, Eicher Motors, Swaraj Mazda etc. These oils are also recommended for earth Moving equipments, Bull dozers, and stationery diesel engines.

Performance Claims:

- *IPOL MTC DIESEL SUPER oils* are manufactured to meet :
- API CF/ CD/ SF
- U.S. MIL-L-2104C
- MACK T-7 pass
- IS:13656-2002 Type E-DL 3.

Performance Benefits:

IPOL MTC DIESEL SUPER oils offer the following benefits :

- Long drain engine oil.
- Reduces wear & tear of engine components
- Keeps piston clean
- Extends engine re-build life
- Retards soot induced oil thickening

Product Data

Typical Results: IPOL MTC Diesel Super Oil

Sr. No.	Characteristics	Test Method IS 1448	Results				
			10W	20	30	40	50
1	Appearance	Visual	Clear & Bright				
2	Kinematic Viscosity cSt @ 100°C	P: 25	5.0 Min.	6 - 8	10 - 12	13 - 15	17 - 19
3	Viscosity Index, min.	P: 56	100	95	95	90	90
4	Flash Point (COC), °C min.	P: 69	190	200	215	220	225
5	Pour Point, °C max.	P: 10	(-) 27	(-)9	(-)6	(-)6	(-)6
6	Evaporative loss % max.	P:136	20	15	10	10	10
7	TBN, mg KOH/gm	P: 86	9.0				
8	Sulphated Ash % mass	P: 4	1.6 Max				
9	Foaming tendency /stability ml./ml./seq I	P: 67	10/Nil				

The above data is typical & does not constitute a specification. The information provided is not to be taken as a warranty or representation for which we assume no legal responsibility, nor as permission or recommendation to practice any attended location or otherwise. It is solely offered for your consideration, investigation and verification.