

IPOL ENHANCO WIRE DRAW 32 L

Description:

IPOL ENHANCO WIRE DRAW 32 L is chlorinated and sulphurised medium viscosity oil fortified with anti-wear and extreme pressure performance additives. The product is found to be excellent in high speed drawing for various gauges with excellent surface finish and improved die life. The product is recommended for all type of Steel Wires. The product is not suitable for Non ferrous wires.

Benefits:

IPOL ENHANCO WIRE DRAW 32 L offers following benefits.

- Excellent lubrication
- Good EP/AW properties
- Excellent thermal stability
- Suitable for medium load as well as for severe load.
- Non misting
- Proven Product.

Storage and Packaging:

IPOL ENHANCO WIRE DRAW 32 L can be supplied either in 210 litre non returnable MS drums or in bulk.

The product should be preferably stored indoors in dry conditions and protected from extreme temperatures. In case the drums are stored outside, adequate precaution needs to be taken to cover them for avoiding any rain water contamination.

Safety and Precautions:

IPOL ENHANCO WIRE DRAW 32 L is unlikely to present any significant health hazard when proper personal and industrial hygiene are maintained.

Product Data

Typical Results: IPOL Enhenco Wire Draw 32 L

Properties	Method IS 1448	Units	Value
Appearance	Visual	-	Amber
Kinematic viscosity	P:25	[cSt, 40°C]	28 - 34
Kinematic Viscosity	P:25	[cSt, 100°C]	4.5 - 7.5
Viscosity Index, min.	P:56		140
Density @ 30°C	ASTM D - 1298	[g/cm ³ , 30°C]	To be reported
Flash point (COC.)°C min.	P:69	[°C]	Min. 180
Copper Strip Corrosion at 120° C, 1 hr.	ASTM D - 130	[°C]	Passes
4 Ball test 800 kgs	ASTM D 2596	Kg	> 800

Note: The information provided is not to be taken as a warranty or representation for which we assume no legal responsibility, nor as permission or recommendation to practice any attended location or otherwise. It is solely offered for your consideration, investigation and verification.

Spltech/05-20/0110

Page 2 of 2