

Product Data

IPOL ENHANCO WIRE DRAW 260 L

IPOL ENHANCO WIRE DRAW 260 L is chlorinated and sulphurised high viscosity oil fortified with anti-wear and extreme pressure performance additives. The product is found to be excellent in high speed drawing for various gauges with excellent surface finish and improved die life. The product is recommended for all type of medium gauge Steel Wires. The product is not suitable for Non ferrous wires.

IPOL ENHANCO WIRE DRAW 260 L offers following benefits.

- Excellent lubrication
- Good EP/AW properties
- Excellent thermal stability
- Suitable for medium load as well as for severe load.
- Non misting
- Proven Product.

Specification

Properties	Method	Units	Value
Appearance	Visual	-	Bright & Clear
Kinematic viscosity	ASTM D – 445	[cSt, 40°C]	270
Kinematic Viscosity	ASTM D – 445	[cSt, 100°C]	23
Viscosity Index			104
Density @ 30°C	ASTM D – 1298	[g/cm ³ , 30°C]	To be reported
Flash point (COC.)	ASTM D – 92	[°C]	Min. 180
Copper Strip Corrosion at 120° C, 1 hr.	ASTM D – 130	[°C]	4C
4 Ball test 200 kgs 1 min.	ASTM D 2596	-	Passes

Spltech/05.99/1 of 2/ 1009

Sah Petroleums Limited

406/407, Embassy Centre, Nariman Point, Mumbai – 400 021, India. Tel: +91 22 66301911, Fax: +91 22 22875751.
Email Id: ipol@sahpetroleums.com Website: www.sahpetroleums.com

Product Data

Storage and Packaging

IPOL ENHANCO WIRE DRAW 260 L can be supplied either in 210 liters non returnable drums or in bulk.

The product should be preferably stored indoors in dry conditions and protected from extreme temperatures. In case the drums are stored outside, adequate precaution needs to be taken to cover them for avoiding any rain water contamination.

Safety and Precautions

IPOL ENHANCO WIRE DRAW 260 L is unlikely to present any significant health hazard when proper personal and industrial hygiene are maintained.

Note: The information provided is not to be taken as a warranty or representation for which we assume legal responsibility, nor as permission or recommendation to practice any attended location or otherwise. It is solely offered for your consideration, investigation and verification.

Spltech/05.99/2 of 2/ 1009

Sah Petroleums Limited

406/407, Embassy Centre, Nariman Point, Mumbai – 400 021, India. Tel: +91 22 66301911, Fax: +91 22 22875751.
Email Id: ipol@sahpetroleums.com Website: www.sahpetroleums.com